



# OX Connector app

*Release 3.0.0*

**Univention GmbH**

**Sep 29, 2025**

The source of this document is licensed under [GNU Affero General Public License v3.0](#) only.

# CONTENTS

<b>1</b>	<b>Installation</b>	<b>3</b>
<b>2</b>	<b>Usage</b>	<b>7</b>
<b>3</b>	<b>Configuration</b>	<b>11</b>
<b>4</b>	<b>Architecture</b>	<b>19</b>
<b>5</b>	<b>Limitations</b>	<b>23</b>
<b>6</b>	<b>Troubleshooting</b>	<b>25</b>
<b>7</b>	<b>Changelog</b>	<b>33</b>
	<b>Bibliography</b>	<b>41</b>
	<b>Index</b>	<b>43</b>



Welcome to the documentation about the **OX Connector** app. The app installs a connector to provision selected users and groups to a remote OX App Suite installation through the OX SOAP API. The app **doesn't** install OX App Suite to UCS (Univention Corporate Server).

This document addresses system administrators, who:

- operate UCS and OX App Suite.
- want to centrally manage users and groups in UCS.
- want to provision permitted users to OX App Suite.

This document covers the following topics:

1. [Installation](#) (page 3) about prerequisites and how to install with web browser and command-line.
2. [Configuration](#) (page 11) with a reference list about the app settings of the OX Connector app.
3. [Architecture](#) (page 19) of the app, how the connector works and the connector cache.
4. [Limitations](#) (page 23) of the app.
5. [Troubleshooting](#) (page 25) about log files, health check, queuing and rebuild the cache.
6. [Changelog](#) (page 33) about what changed in the different app versions.

This document doesn't cover the following topics:

- Installation, setup and usage of OX App Suite, see *App Suite Admin Guide 7.10.5* [1].
- Installation, setup and usage of UCS, see *UCS 5.2 Manual* [2].

To understand this document, you need to know the following concepts and tasks:

- Use and navigate in a remote shell on Debian GNU/Linux derivative Linux distributions like UCS. For more information, see [Shell and Basic Commands](#)<sup>1</sup> from *The Debian Administrator's Handbook*, Hertzog and Mas [3].
- [Manage an app through Univention App Center](#)<sup>2</sup> in *UCS 5.2 Manual* [2].

Your feedback is welcome and highly appreciated. If you have comments, suggestions, or criticism, please [send your feedback](#)<sup>3</sup> for document improvement.

---

<sup>1</sup> <https://www.debian.org/doc/manuals/debian-handbook/short-remedial-course.en.html#sect.shell-and-basic-commands>

<sup>2</sup> <https://docs.software-univention.de/manual/5.2/en/software/further-software.html#computers-softwareselection>

<sup>3</sup> <https://www.univention.com/feedback/?ox-connector=generic>



## INSTALLATION

The **OX Connector** app connects the UCS identity management with the OX App Suite database. For more information about how it works, see *How the connector works* (page 20).

### 1.1 Prerequisites

Before you as administrator can install the **OX Connector** app, you need to make sure that your environment fulfills the prerequisites.

#### 1.1.1 OX App Suite server

For the *OX App Suite* server, you must ensure the following prerequisites:

1. The environment requires an installed OX App Suite instance. This documentation assumes that an OX App Suite installation already exists.

For limitations about the **OX App Suite** app from Univention App Center and the connector, see *Integration of OX Connector and OX App Suite app* (page 23).

For installation of OX App Suite, see *App Suite Admin Guide 7.10.5* [1].

2. The OX App Suite instance must allow SOAP requests, so that the UCS system, where the *administrator installs the OX Connector app* (page 4), can connect to `/webservices`.
3. You have to set up an administrator user in OX App Suite that can create OX contexts.

The OX Connector can manage OX contexts. The installation of the **OX Connector** app needs username and password for that user and references them in the setting `OX_MASTER_ADMIN` (page 12) and `OX_MASTER_PASSWORD` (page 12).

For manually managing OX contexts without the OX Connector, see *Contexts* (page 7).

4. Since version 2.2.0, OX must allow the use of duplicated *displaynames*. To enable it, add the following lines to the `user.properties` file.

```
com.openexchange.user.enforceUniqueDisplayName=false
com.openexchange.folderstorage.database.preferDisplayName=false
```

#### Note

This is configured by default in version 7.10.6-ucs7 of **OX App Suite** from the App Center.

#### 1.1.2 UCS domain

Another prerequisite needs some steps in the UCS domain. To use the **OX Connector** app, the central LDAP directory needs the *referential integrity* overlay enabled. The overlay ensures that UDM objects provided by the OX Connector keep their integrity and always reference user objects correctly in the LDAP directory.

If you install **OX Connector** on Primary Directory Node, the app already takes care of the necessary step. No further action required.

If you install **OX Connector** on other [UCS system roles](#)<sup>4</sup> than the Primary Directory Node, you need to run the following commands:

Listing 1.1: Activate OpenLDAP *referential integrity* overlay on Primary Directory Node.

```
$ ucr set ldap/refint=true
$ service slapd restart
```

For more information about the *referential integrity* overlay, see *Referential Integrity in OpenLDAP Software 2.4 Administrator's Guide* [4].

## 1.2 Installation on UCS system

As administrator, you can install the **OX Connector** app like any other app with Univention App Center. Make sure to fulfill the *Prerequisites* (page 3).

UCS offers two different ways for app installation:

- With the web browser in the UCS management system
- With the command-line

For general information about Univention App Center and how to use it for software installation, see [Univention App Center](#)<sup>5</sup> in *UCS 5.2 Manual* [2].

### 1.2.1 With the web browser

To install **OX Connector** from the UCS management system, use the following steps:

1. Use a web browser and sign in to the UCS management system.
2. Open the *App Center*.
3. Select or search for *OX Connector* and open the app with a click.
4. To install the OX Connector, click *Install*.
5. Adjust the *App settings* to your preferences. For a reference, see *Configuration* (page 11).
6. To start the installation, click *Start Installation*.

#### Note

To install apps, the user account you choose for login to the UCS management system must have domain administration rights, for example the username `Administrator`. User accounts with domain administration rights belong to the user group `Domain Admins`.

For more information, see [Delegated administration for UMC modules](#)<sup>6</sup> in *UCS 5.2 Manual* [2].

### 1.2.2 With the command-line

To install the **OX Connector** app from the command-line, use the following steps:

1. Sign in to a terminal or remote shell with a username with administration rights, for example `root`.

---

<sup>4</sup> <https://docs.software-univention.de/manual/5.2/en/domain-ldap/system-roles.html#system-roles>

<sup>5</sup> <https://docs.software-univention.de/manual/5.2/en/software/app-center.html#software-appcenter>

<sup>6</sup> <https://docs.software-univention.de/manual/5.2/en/central-management-umc/delegated-administration.html#delegated-administration>



2. Adjust the settings to your preferences with the appropriate installation command. For a reference, see [Configuration](#) (page 11). To pass customized settings to the app during installation, see the following command template:

```
$ univention-app install ox-connector --set $SETTING_KEY=$SETTING_VALUE
```

**Example:**

```
$ univention-app install ox-connector --set \  
OX_MASTER_ADMIN="oxadminmaster" \  
OX_MASTER_PASSWORD="some secure password" \  
LOCAL_TIMEZONE="Europe/Berlin" \  
OX_LANGUAGE="de_DE" \  
DEFAULT_CONTEXT="10" \  
OX_SMTP_SERVER="smtp://my-smtp.example.com:587" \  
OX_IMAP_SERVER="imap://my-imap.example.com:143" \  
OX_SOAP_SERVER="https://my-ox.example.com"
```

**Note**

The installation process asks for the password of the domain administrator Administrator. To use another username and password for installation, pass different values with the options `--username` and `--pwdfile`. For more information, see **univention-app install -h**.



## USAGE

The **OX Connector** centrally manages users, groups, OX contexts, OX access profiles and functional accounts with the web based management system in UCS. This section shows how.

To follow the tasks, you need to sign-in to Univention Management Console (UMC) with a user account with domain administration rights. For more information, see [Delegated administration for UMC modules](#)<sup>7</sup> in *UCS 5.2 Manual* [2].

### 2.1 Contexts

OX App Suite uses *contexts* to collect users, groups, and resources for collaboration in a virtual space. Data from one context isn't visible to other contexts. For more information about contexts, see *App Suite Context management* [5].

To view, add, update, or delete a context, you navigate to *Domain ▶ OX Contexts* in UMC.

#### Note

If you don't want the OX Connector to manage *contexts*, you can manually manage them in OX App Suite, as long as you maintain the *context* configuration for the OX Connector in the `/var/lib/univention-appcenter/apps/ox-connector/data/secrets/contexts.json`.

This approach doesn't require to share the credentials for the OX context administrator.

### 2.2 Users

To enable users for OX App Suite, administrators can either create user accounts or update existing ones.

To enable a user account for OX App Suite, run the following steps:

1. Navigate to *Users ▶ Users* in UMC and click to open.

To create a user account:

2. Click *Add* to create a user account and select the *User template open-xchange groupware account*.
3. Click *Next*.
4. Fill out the required fields. To fill out more attributes, click *Advanced*.
5. When finished, click *Create user*.

To update a user account:

2. Click the username for the user you want to update.
3. Go to the *Apps* tab and activate the *Open-Xchange* checkbox. The tab *Open-Xchange* appears.
4. Define an email address for the user at *General ▶ Primary e-mail address (mailbox)*.
5. Click *Save*.

---

<sup>7</sup> <https://docs.software-univention.de/manual/5.2/en/central-management-umc/delegated-administration.html#delegated-administration>

**See also**

User management<sup>8</sup> in *UCS 5.2 Manual* [2].

## 2.3 Groups

The **OX Connector** app adds a group to the same context as the group members. When the last group member leaves the group, the connector removes the group from OX App Suite.

To enable a group for OX App suite, run the following steps:

1. Navigate to *Users* ▶ *Groups* in UMC and click to open.

To create a group:

2. Click *Add* to create a group.
3. On the *General* tab, fill out the required fields and add users as group members.
4. Go to the *OX App Suite* tab and activate the *Activate Group in OX*.
5. Click *Create group*.

To update a group:

2. Click a group to edit.
3. The UDM module *Groups* automatically enables *Activate Group in OX*, when you edit a group. UMC displays a notification.

If you don't want to enable the group, clear the checkbox *Activate Group in OX* on the *OX App Suite* tab.

4. Click *Save*.

**Warning**

When you as administrator update a group, that already is a group in OX App Suite, and you clear the checkbox *Activate Group in OX* on the *OX App Suite* tab, the connector removes this group from OX App Suite.

To update a group from the command-line, run the following command:

```
$ udm groups/group modify --dn $dn_of_group --set isOxGroup=OK
```

To remove a group from OX App Suite:

2. Click a group to edit.
3. Go to the *OX App Suite* tab and clear the checkbox *Activate Group in OX*.
4. Click *Save*.

To remove the group from OX App Suite through command-line, run the following command:

```
$ udm groups/group modify --dn $dn_of_group --set isOxGroup=Not
```

**See also**

Group management<sup>9</sup> in *UCS 5.2 Manual* [2].

---

<sup>8</sup> <https://docs.software-univention.de/manual/5.2/en/user-management/index.html#users-general>

<sup>9</sup> <https://docs.software-univention.de/manual/5.2/en/groups.html#groups>

## 2.4 Access profiles

The OX Connector already provides ready-to-use *access profiles* for OX App Suite users. Administrators can create custom *access profiles* in UMC in the *LDAP directory* module at *Domain ▶ LDAP directory* at the directory location `open-xchange/accessprofiles/`.

For limitations about plausibility verification, see *No plausibility validation in access profile rights* (page 24).

## 2.5 Functional accounts

Added in version 2.0.0.

OX App Suite shares functional mailboxes among other users in the same context.

With the UDM (Univention Directory Manager) module `oxmail/functional_account` administrators can add, update or delete objects for functional accounts. OX App Suite users with the same functional account share the read status. Emails to addresses of functional accounts show up in the OX Mail view for every user where administrators granted the permission.

### 2.5.1 Default LDAP position for functional accounts

Added in version 2.2.12.

When you create a new `oxmail/functional_account` object in UMC (Univention Management Console) the default position for these new objects in the directory tree is `cn=functional_accounts,cn=open-xchange,$LDAP_BASE`.

However, you can add additional default containers for the `oxmail/functional_account` so that UMC will ask for a position before creating the new object.

In the UMC module *LDAP directory* open the container `univention` in the tree view (left) and then open the object `default_containers` in the object list (right). Click on `OX App suite` and add additional default containers to the list of `Default container for OX functional accounts`. The values are LDAP DN's of existing container objects in your LDAP directory, which must include the LDAP base DN.

## 2.6 Resources

OX App Suite uses *OX Resources* to manage resources like rooms or equipment that users can book for appointments. For more information about resource management, see *App Suite Resource management* [6].

To view, add, update, or delete a resource, you navigate to *Domain ▶ OX Resources* in UMC.



## CONFIGURATION

The following reference shows the available settings for the **OX Connector** app.

### 3.1 App Settings

#### OX\_SOAP\_SERVER

Defines the server that has OX App Suite installed. Provide the protocol and the FQDN, for example `https://ox-app-suite.example.com`.

[OX\\_SOAP\\_SERVER](#) (page 11) instructs the OX Connector app in the Docker container, where it must look for the OX App Suite system. The Docker container must resolve the FQDN.

Required	Type	Initial value
Yes	String	<code>https://\$hostname.\$domainname</code>

For secure connections with HTTPS the Docker container needs to validate the certificate.

#### Note

If the OX App Suite instance uses a self-signed certificate or a certificate it can't validate, the OX Connector container needs the root certificate for validation. You need to store the self-signed certificate files in the `/var/lib/univention-appcenter/apps/ox-connector/data/conf/ca-certificates/` directory. For details, see [Import additional CA certificates](#) (page 18).

#### OX\_IMAP\_SERVER

Defines the default IMAP server for new users, if not explicitly set at the user object.

Required	Type	Initial value
Yes	String	<code>imap://\$hostname.\$domainname:143</code>

#### OX\_SMTP\_SERVER

Defines the SMTP server for new users, if not explicitly set at the user object.

Required	Type	Initial value
Yes	String	<code>smtp://\$hostname.\$domainname:587</code>

#### DEFAULT\_CONTEXT

Defines the default context for users. The OX Connector doesn't create the `DEFAULT_CONTEXT` automatically. You as administrator must ensure, the default context exists before the OX Connector provisions the first user. To create a context, see [Contexts](#) (page 7).

Required	Type	Initial value
Yes	Integer	10

**OX\_LANGUAGE**

Defines the default language for new users

Required	Type	Initial value
Yes	String	de_DE

**LOCAL\_TIMEZONE**

Defines the default timezone for new users

Required	Type	Initial value
Yes	String	Europe/Berlin

**OX\_MASTER\_ADMIN**

Defines the user for the OX App Suite administrator user, also called *OX Admin user*. This user can create, modify, and delete contexts. The user must already exist. The administrator defines the username for the *OX Admin user* during the installation of OX App Suite.

Required	Type	Initial value
Yes	String	oxadminmaster

**OX\_MASTER\_PASSWORD**

Defines the password for the *OX Admin user*.

Required	Type	Initial value
No	Password	N/A

**OX\_IMAP\_LOGIN**

Defines the value that is used by OX to log in to the user's inbox. If this value is empty it is set to the user's mail address.

Required	Type	Initial value
No	String	N/A

In cases where you use single sign-on, you need to append this variable with an asterisk and the mail server's master user. For Dovecot, the master user is `*dovecotadmin`. In this case, you need to set `OX_IMAP_LOGIN` to `'{*}dovecotadmin'`. The OX Connector interprets the curly braces as a template for the primary email address. You can add any user attribute inside the curly braces if needed, for example, `{username}` while empty braces are for `primaryMailAddress`.

**OX\_FUNCTIONAL\_ACCOUNT\_LOGIN\_TEMPLATE**

A template that defines the value which is used by OX to log in to the functional account inbox. If this value is empty it is set to a concatenation of the functional account LDAP entry UUID and the user LDAP uid.

This template can include the functional account entry UUID (*fa\_entry\_uuid*), the functional account email address (*fa\_email\_address*) and any OX user UDM property (including the user's *entry\_uuid* and *dn*). Every



UDM property used in this template must be enclosed by `{{ }}` e.g `{{fa_entry_uuid}}{{username}}`. Multiple values can optionally be separated by other text.

Required	Type	Initial value
No	String	N/A

#### Note

If the UCS OX App Suite is used, this app setting can be left empty, which is equivalent to using the value `{{fa_entry_uuid}}{{username}}`.

OX Connector installations that previously only used the functional account entry UUID should configure this app setting to `{{fa_entry_uuid}}`.

Some examples:

```
"{{fa_entry_uuid}}::{{entry_uuid}}" # Functional account entry UUID and
↳user UUID separated by two colons.
"{{username}}+{{fa_entry_uuid}}+{{dn}}" # username, functional account
↳entry UUID and user dn separated by a '+'
"{{fa_email_address}}*dovecotadmin" # Concatenation of functional account's
↳mail address and the string *\dovecotadmin
```

#### Note

In cases where SSO is to be used, this variable has to be appended with an asterisk and the mail server's master user. For Dovecot this would be `*dovecotadmin`. In this case `OX_FUNCTIONAL_ACCOUNT_LOGIN_TEMPLATE` can be set to `'{{fa_email_address}}*dovecotadmin'`. The resulting login value for the functional account would then look like this:

```
myfunctional_account@maildomain.de*dovecotadmin
```

### OX\_USER\_IDENTIFIER

Defines which UDM user property is used as the unique user identifier for OX. If this app setting is not set the **OX Connector** will use the `username` property by default.

Required	Type	Initial value
No	String	N/A

#### Note

Only a UDM user property that contains a **single value** which is **not None** (mandatory UDM property) is a valid option. In case a UDM user property that contains an empty value or a list of values is specified, the **OX Connector** will enter an error state which needs to be resolved manually by simply setting a valid value.

### OX\_GROUP\_IDENTIFIER

Defines which UDM group property is used as the unique group identifier for OX. If this app setting is not set the **OX Connector** will use the `name` property by default.

Required	Type	Initial value
No	String	N/A

**Note**

Only a UDM group property that contains a **single value** which is **not None** (mandatory UDM property) is a valid option. In case a UDM group property that contains an empty value or a list of values is specified, the **OX Connector** will enter an error state which needs to be resolved manually by simply setting a valid value.

**OX\_CONNECTOR\_LOG\_LEVEL**

Defines the log level for the ox-connector app. If this app setting is not set the **OX Connector** will use `INFO` by default.

Required	Type	Initial value
No	String	INFO

**OX\_ENABLE\_DEPUTY\_PERMISSIONS**

Enables the provisioning of OX deputy permissions. Administrators then can set, modify, or delete deputy permissions for users in the UMC.

For example, administrators can grant `user01` the roles *Viewer*, *Editor*, and *Author* for the calendar and mail module for `user01`. Furthermore, `user01` can send emails on behalf of `user02`.

The default value is `False`. To enable the feature, set the app setting `OX_ENABLE_DEPUTY_PERMISSIONS` (page 14) to `True`.

To see the feature in the UMC, you need to enable the UMC representation for the extended attribute either after the app installation, or after the configuration. Run the command in [Listing 3.1](#) either on the *UCS Primary Directory Node* or a *UCS Backup Directory Node*.

Listing 3.1: Activate the UMC representation of the enabled deputy permission feature.

```
$ univention-directory-manager \
  settings/extended_attribute modify \
  --dn "cn=oxDeputyPermissionGivenTo,cn=open-xchange,cn=custom attributes,
  ↪cn=univention,$(ucr get ldap/base)" \
  --set disableUDMWeb="0"
```

Required	Type	Initial value
No	Boolean	False

**Important**

The *Deputy Permissions* feature requires OX App Suite version  $\geq 8$ .

Users can modify the deputy permissions on their own in **OX App Suite**. The provisioning in the **OX Connector** app through UCS overwrites these settings.

**See also**

**Deputy permissions : Technical Documentation**<sup>10</sup>  
for more information about OX deputy permissions.

**OX\_CONNECTOR\_STOP\_ON\_ERROR**

Changes the behavior of the app **OX Connector** when it handles errors during synchronization. It can either stop on any error and retry the failed action until it succeeds or the Administrator resolves it manually (**True**). The App can also continue with other actions in its queue and instead put the failed action “aside”, meaning it will no longer interfere with the execution of the connector, but can be examined by the Administrator at any later stage (**False**). See also *Troubleshooting* (page 25).

Required	Type	Initial value
No	Boolean	True

## 3.2 Univention Configuration Registry variables

**ox/context/id**

The app setting **DEFAULT\_CONTEXT** (page 11) sets the value of the Univention Configuration Registry variable **ox/context/id** (page 15).

Upon installation of the app **OX Connector**, the OX Connector creates the extended attribute **oxContext** and uses the value from **ox/context/id** (page 15) as initial value for the extended attribute **oxContext**.

When an administrator creates a new user account that the OX Connector synchronizes, UDM sets the OX context for the user account to value of the extended attribute **oxContext**.

**Caution**

The UCR variable **ox/context/id** (page 15) **isn't** for manual usage.

Changing the variable **doesn't** change the OX context on existing user accounts.

Changing the value of the app setting **DEFAULT\_CONTEXT** (page 11) does **neither** change **ox/context/id** (page 15) **nor** the extended attribute **oxContext**.

## 3.3 User attribute mapping

Added in version 2.2.9: Modify the mapping between *Open-Xchange* and *UDM* properties.

Since version 2.2.9, you can modify the mapping between *Open-Xchange* and *UDM* properties using the script **change\_attribute\_mapping.py** provided with the app. The script creates a JSON file that stores information about the Open-Xchange properties and other information useful for user provisioning.

Don't modify the file manually, but only with the script. The JSON file locates at `/var/lib/univention-appcenter/apps/ox-connector/data/AttributeMapping.json`. If the file doesn't exist, the OX Connector uses the default mapping defined in `/usr/lib/python3.9/site-packages/univention/ox/provisioning/default_user_mapping.py` inside the Docker container of the app.

The script allows the following operations:

**modify**

performs operations that change the current mapping.

<sup>10</sup> [https://documentation.open-xchange.com/8/middleware/permissions\\_and\\_capabilities/deputy\\_permission.html](https://documentation.open-xchange.com/8/middleware/permissions_and_capabilities/deputy_permission.html)

**restore\_default**

restores the default mapping.

**dump**

writes the current JSON mapping to console.

With the *modify* operation, you can use the following additional operations:

**--set**

Changes the UDM property used for an Open-Xchange property provisioning. [Listing 3.2](#) shows how to set the mapping of the Open Xchange property `userfield01` to the UDM property `description`.

Listing 3.2: Sets the mapping of an Open-Xchange property to an UDM property.

```
$ python3 /var/lib/univention-appcenter/apps/ox-connector/data/resources/  
→change_attribute_mapping.py \  
  modify \  
    --set userfield01 description
```

It's possible to use the `--set` (page 16) arguments multiple times in the same invocation. [Listing 3.3](#) shows an example that sets the mapping of the Open-Xchange properties `userfield01` and `given_name` to the UDM properties `description` and `custom_attribute`.

Listing 3.3: Sets the mapping of multiple Open-Xchange properties to multiple UDM properties.

```
$ python3 /var/lib/univention-appcenter/apps/ox-connector/data/resources/  
→change_attribute_mapping.py \  
  modify \  
    --set userfield01 description \  
    --set given_name custom_attribute
```

**--unset**

Removes the Open-Xchange property from the mapping if it isn't marked as required. You can use it to remove properties from the synchronization.

Listing 3.4: Unset the OX property `userfield01`.

```
$ python3 /var/lib/univention-appcenter/apps/ox-connector/data/resources/  
→change_attribute_mapping.py \  
  modify \  
    --unset userfield01
```

**--set\_alternatives**

Sets alternative UDM properties used for the synchronization if the main one is `None`. [Listing 3.5](#) shows an example to set the theoretical attributes `CustomAttributeUserMail` and `CustomAttributeUserMail2` as alternatives to the Open-Xchange property `email1`.

Listing 3.5: Set theoretical attributes as alternatives to an Open-Xchange property.

```
$ python3 /var/lib/univention-appcenter/apps/ox-connector/data/resources/  
→change_attribute_mapping.py \  
  modify \  
    --set_alternatives email1 CustomAttributeUserMail CustomAttributeUserMail2
```

**--unset\_alternatives**

Unset the current alternatives for an OX property

Listing 3.6: Unset the alternative attributes to the OX property email1.

```
$ python3 /var/lib/univention-appcenter/apps/ox-connector/data/resources/
↪change_attribute_mapping.py \
    modify \
    --unset_alternatives email1
```

If you previously used the attribute mapping feature of the OX App Suite app from the App Center, you can migrate it by running the following command on the UCS system where you installed the OX App Suite. You then use the output of the script as command and run it on the UCS system where the OX Connector is running.

```
python3 <<EOF
from univention.config_registry import ConfigRegistry
ucr = ConfigRegistry()
ucr.load()

changed_mapping_single = {
    'displayname': 'display_name',
    'givenname': 'given_name',
    'surname': 'sur_name',
    'categories': 'employee_type',
    'quota': 'max_quota',
}

changed_mapping_multi = {
    'telephone_business': ['telephone_business1', 'telephone_business2'],
    'telephone_home': ['telephone_home1', 'telephone_home2'],
}

ucr_ldap2ox = ucr.get('ox/listener/user/ldap/attributes/mapping/ldap2ox', '').
↪strip()
ucr_ldap2oxmulti = ucr.get('ox/listener/user/ldap/attributes/mapping/ldap2oxmulti
↪', '').strip()
command = []
if ucr_ldap2ox:
    for entry in ucr_ldap2ox.split():
        value, key = entry.split(':', 1)
        if value is None:
            command.append(f"--unset {changed_mapping_single.get(key, key)}")
        else:
            command.append(f"--set {changed_mapping_single.get(key, key)} {value}")

if ucr_ldap2oxmulti:
    ldap2oxmulti = {}
    for entry in ucr_ldap2oxmulti.split():
        value, key = entry.split(':', 1)
        if value is None:
            for v in changed_mapping_multi.get(key, [key]):
                command.append(f"--unset {v}")
        else:
            for v in changed_mapping_multi.get(key, [key]):
                command.append(f"--set {v} {value}")
if command:
    print("Run the following command on the ox-connector server to update_
↪attribute mapping:")
    print("python3 /var/lib/univention-appcenter/apps/ox-connector/data/resources/
```

(continues on next page)

(continued from previous page)

```
↪change_attribute_mapping.py modify " + " ".join(command))
else:
    print("Nothing to do.")
EOF
```

## 3.4 Import additional CA certificates

Added in version 2.3.0: Allow the connector to import additional CA certificates

The **OX Connector** app in UCS runs as a container with its own CA certificate store. By default, the app imports the UCS root CA certificate into the CA store to enable a secure connection to the UCS LDAP directory. You may need additional CA certificates for the **OX Connector** app, for example, when provisioning to a remote **OX App Suite** installation.

To add certificates to the certificate store in the **OX Connector**, use the following steps on the system where the app is installed:

1. Create the `/var/lib/univention-appcenter/apps/ox-connector/data/conf/ca-certificates/` directory.
2. Copy the CA certificate files in PEM format with the ending `.pem` into this directory. [Listing 3.7](#) shows an example.

Listing 3.7: Examples for additional CA certificates

```
$ file /var/lib/univention-appcenter/apps/ox-connector/data/conf/ca-
↪certificates/*.pem
.../ox-connector/data/conf/ca-certificates/cert1.pem: PEM certificate
.../ox-connector/data/conf/ca-certificates/cert2.pem: PEM certificate
```

3. Manually reconfigure the OX Connector with the command in [Listing 3.8](#). The **OX Connector** app automatically adds the certificates to its certificate store, also during app updates.

Listing 3.8: Manually reconfigure the OX Connector

```
$ univention-app configure ox-connector
```

## ARCHITECTURE

The **OX Connector** app architecture consists of the following elements:

- The operating environment UCS with the App Center and the Docker engine running OX Connector.
- The OX Connector software inside a Docker image.
- The OpenLDAP LDAP directory in UCS as identity management source for OX App Suite.

### 4.1 Overview

The **OX Connector** app consists of a Docker image with all the software needed to provision user identities from UCS identity management to OX App Suite. The OX connector connects to the OX App Suite SOAP API and creates, updates, or deletes object entries in OX App Suite depending on what changed in the UCS LDAP directory with relevance to OX App Suite.




Fig. 4.1: OX Connector app architecture

View focuses on the elements LDAP Directory, Listener, Listener Converter, OX Connector with the provisioning script, OX App Suite, and its SOAP API.

#### LDAP

The OpenLDAP software provides the *LDAP* directory in UCS. The LDAP directory stores all identity and infrastructure data of the UCS domain. For more information, see [LDAP directory](https://docs.software-univention.de/manual/5.2/en/domain-ldap/ldap-directory.html#domain-ldap)<sup>11</sup> in *UCS 5.2 Manual* [2].

---

<sup>11</sup> <https://docs.software-univention.de/manual/5.2/en/domain-ldap/ldap-directory.html#domain-ldap>

### Listener

The App Center creates a *Listener* module for the **OX Connector** app, when it installs the app on a UCS system. The *Listener* writes the `UniventionObjectIdentifier` of the LDAP object that changed, in JSON format to `/var/lib/univention-appcenter/listener/ox-connector/timestamp.json`. Each change creates one file.

### Listener Converter

The *Listener Converter* is a services running on UCS with the following responsibility:

1. Process the JSON files from the *Listener* ordered by the timestamp in the filename.
2. Request the LDAP object attributes through UDM for each `UniventionObjectIdentifier`.

The converter writes the results in JSON format to `/var/lib/univention-appcenter/apps/ox-connector/data/listener/timestamp.json`.

### OX Connector

*OX Connector* connects the UCS identity management with OX App Suite. The connector receives data about changes in the LDAP directory. A *Script* handles the data, processes it and sends it to the *SOAP API* in OX App Suite.

### Script

The *Script* runs inside the Docker container of the OX Connector. It handles the files in JSON format from the *Listener Converter*, consumes it and sends data to the *SOAP API*.

The *Script* doesn't run multiple times at the same time.

### OX App Suite

*OX App Suite* is the groupware and collaboration software from Open-Xchange.

### SOAP API

OX App Suite uses *SOAP*<sup>12</sup> as network protocol to receive data and run remote procedure calls. The connector uses the SOAP API to create, update, or delete object entries in OX App Suite.

## 4.2 How the connector works

The OX Connector reacts on changes in the LDAP directory in UCS and relies on modules in the Univention Directory Manager (UDM) modules. UDM is a layer on top of the LDAP directory in UCS.

UCS provides the following UDM modules:

- `users/user`
- `groups/group`

The OX Connector provides the following UDM modules:

- `oxmail/oxcontext`
- `oxresources/oxresources`
- `oxmail/accessprofile`

The OX Connector reacts on changes to the listed UDM modules and sends data to the SOAP API in OX App Suite.

### 4.2.1 Access profiles

Upon changes in the UDM module `oxmail/accessprofile`, the connector rewrites the local file `/var/lib/univention-appcenter/apps/ox-connector/data/ModuleAccessDefinitions.properties` and doesn't send data to the SOAP API in OX App Suite. The module handles the user rights and roles in OX App Suite. Administrators find the *access profiles* in UMC in the module LDAP directory at *open-xchange* ▶ *accessprofile*.

---

<sup>12</sup> <https://en.wikipedia.org/wiki/SOAP>



## 4.2.2 Provisioning

In detail, the provisioning has the following steps, see Fig. 4.2:




Fig. 4.2: Provisioning procedure

1. The *Listener* writes one file per change.
2. The *Listener Converter* writes one file per change with the LDAP object attributes.
3. The *Listener Converter* triggers the *Script* in the OX Connector Docker container.
4. In the Docker container, the *Script* consumes all the JSON files from the *Listener Converter*.
5. After the *SOAP API* received the data and processed them successfully, the *Script* deletes each JSON file.
6. The *Listener Converter* waits for 5 seconds and restarts at step 2.

For more information about the file contents of the *Listener* and *Listener Converter*, see *Overview* (page 19).

## 4.3 Provisioned attributes

The **OX Connector** provisions a lot of attributes to OX App Suite. A detailed description is beyond the scope of this document.

The OX Connector comes with the source code. The user attributes for provisioning locate in the function `update_user()` in `univention-ox-provisioning/univention/ox/provisioning/users.py` inside the Docker container. To view the attributes, for example with `vim`, run the following command on the UCS system with OX Connector installed. Replace `$version` with the proper Python version used in the Connector:

Listing 4.1: Example for how to view the definition of provisioned attributes.

```
$ univention-app shell ox-connector \
  cat /usr/lib/python"$version"/site-packages/univention/ox/provisioning/users.py \
  | vim -
```

Likewise, the attributes for groups, context, and resources locate in the respective source files in the `update_*` function.

## 4.4 Database of old entries

Added in version 3.0.0.

*OX App Suite* creates an *internal ID* for every user object it creates or updates. The OX Connector saves this *internal ID* in its own database, when it processed the objects without errors. The connector doesn't store that ID in the UCS LDAP directory, but maintains a database in which it stores the data old object's it processed for later reference (i.e., for retrieving the *internal ID*)

The database files is located at `/var/lib/univention-appcenter/apps/ox-connector/data/listener/ox-connector.db`. The table is named *old*. Administrators are highly advised to use the CLI the App provides to manipulate this database, see *CLI to monitor the current state* (page 25).

When the *Listener Converter* updates groups in OX App Suite, the request to the *SOAP API* must include the internal ID of all group members. The connector would need to ask the database of OX App Suite for the *internal ID* of each group member, involving network requests and database queries. To speed up the processing, the OX Connector uses the *internal ID* from the database.

## **LIMITATIONS**

To ensure a smooth operation of the **OX Connector** app on UCS, you as administrator need to know the following limitations.

### **5.1 Integration of OX Connector and OX App Suite app**

Starting with version 2.1.2, Univention supports the use of the **OX Connector** for the **OX App Suite** app from Univention App Center. The **OX Connector** handles the provisioning, while the **OX App Suite** delivers the actual groupware.

However, the **OX Connector** needs administrative credentials to create context objects in the database for the **OX App Suite**. The installation process doesn't know these credentials. Therefore, you need to verify the configuration of the **OX Connector** after you have successfully installed **OX App Suite**. The reconfiguration runs automatically if, and only if, both apps locate on the same UCS system.

If not, you find the password in the file `/etc/ox-secrets/master.secret` on the UCS system running **OX App Suite**. The username of the administrative account is `oxadminmaster`. You need to set the credentials in the app settings of the **OX Connector**, see [Configuration](#) (page 11).

### **5.2 How the Connector handles faulty items**

The **OX Connector** knows two strategies how to handle faulty items it can't synchronize. You can choose which strategy to use: [App Settings](#) (page 11).

#### **5.2.1 OX Connector continues after faulty items**

When the **OX Connector** encounters a faulty queue item that it can't process, it continues with the next queue items. The **OX Connector** puts the faulty item aside for the Administrator to examine at a later stage. The problem is written in the log file, see [Log files](#) (page 25).

The app ships a CLI to manage the list of errors, see [CLI to monitor the current state](#) (page 25).

As administrator, you need to monitor the list of errors manually and decide what to do (delete or retry). Meanwhile, the **OX Connector** continues to process data it gets from the [Listener](#).

Note that certain errors are excluded from that behavior. When the **OX Connector** encounters a problem that hints to a network error, it retries this one task over and over again as continuing will most probably result in the same error for all items anyway. Synchronizing objects from the UDM module `oxmail/oxcontext` will also be retried as these objects are extremely important to be in sync. All following items in the queue will likely fail, therefore the app does not just continue in this case. The strategy of stopping instead of continuing is also described in the next chapter [OX Connector stops at faulty items](#) (page 23).

#### **5.2.2 OX Connector stops at faulty items**

When the **OX Connector** encounters a faulty queue item that it can't process, it stops the provisioning at the item and the problematic task in the [Listener Converter](#) log file, see [Log files](#) (page 25).

Despite the stop, the *Listener* continues to add items to the queue. After the administrator removed the faulty queue item, the Listener Converter continues to process the queue and also takes care of the added items.

As administrator, you need to resolve that conflict manually when it happens, see *Provisioning stops working* (page 27). After the conflict resolution, the connector continues to process the provisioning queue.

### 5.3 No plausibility validation in access profile rights

The **OX Connector** app doesn't evaluate permission level for created *access profiles* and tries to create any access profile.

For more information, see *OX App Suite Permission Level*<sup>13</sup>.

---

<sup>13</sup> [https://oxpedia.org/wiki/index.php?title=AppSuite:Permission\\_Level](https://oxpedia.org/wiki/index.php?title=AppSuite:Permission_Level)

## TROUBLESHOOTING

When you encounter problems with the operation of the **OX Connector** app, this section provides information where you can look closer into and to get an impression about what's going wrong.

### 6.1 Log files

The **OX Connector** app produces different logging information in different places.

**Listener Converter:** `/var/log/univention/listener_modules/ox-connector.log`

Contains log information from the *Listener Converter* about create, update and delete actions of objects.

It also shows warnings and errors when the OX Connector configuration isn't correct, or the connector can't establish a connection to the *SOAP API*.

**Database management script:** `/var/lib/univention-appcenter/apps/ox-connector/data/db.log`

Contains log information from the *Database management script* that is described below.

**App Center:** `/var/log/univention/appcenter.log`

Contains log information around activities in the App Center.

The App Center writes OX Connector relevant information to this file, when you run app lifecycle tasks like install, update and uninstall or when you change the app settings.

**Domain join:** `/var/log/univention/join.log`

Contains log information from the join processes. When the App Center install OX Connector, the app also joins the domain.

### 6.2 Checking the Listener

Before checking the OX Connector, you may want to have a look at the connection between the *Listener* and the *Listener Converter*. The Listener should create files and the Listener Converter should translate these files rather quickly.

Listing 6.1: Verify the number of unprocessed files for the *Listener*.

```
$ DIR_LISTENER="/var/lib/univention-appcenter/listener/ox-connector"
$ ls -l "$DIR_LISTENER"/*.json 2> /dev/null | wc -l
0
```

If files here are not created upon a change or are piling up, this indicates a problem in the Listener or Listener Converter. See *Log files* (page 25).

### 6.3 CLI to monitor the current state

The OX Connector ships a command-line interface that you can use to query and manipulate the database it uses to keep track of current tasks, objects already synced and errors it may have found.

Listing 6.2: List all commands of the CLI.

```
$ /usr/sbin/univention-ox-connector-task-management --help
```

The tool operates on the **SQLite** database `/var/lib/univention-appcenter/apps/ox-connector/data/listener/ox-connector.db`. The terminology of the tool is as follows:

**Tasks**

A database table managed by the OX Connector. A row represents an active task. The OX Connector iterates over all tasks and synchronizes them to the OX App Suite.

**Old**

A database table managed by the OX Connector. A row represents the state of an item at the moment it was successfully synchronized. It is more or less a copy of a former task. Needed when certain items are synchronized and reference other items (e.g., when synchronizing a group that contains users). Also used for faster look-ups by storing the database ID given by OX.

**Morgue**

A database table managed by the OX Connector. A row represents a failed task. It was moved automatically or manually to this table and is not actively processed by the OX Connector. Administrators can examine the items in the morgue and decide how to proceed with them (see below).

### 6.3.1 Health check

First, have a look at the log file for the *Listener Converter* and look for warnings and errors, see *Log files* (page 25).

Second you can get a brief summary of current tasks. This can indicate if the OX Connector can process the items fast enough or at all.

Listing 6.3: Show all tasks the OX Connector is yet to process.

```
$ /usr/sbin/univention-ox-connector-task-management summarize-tasks
$ /usr/sbin/univention-ox-connector-task-management search-tasks
```

Third, you can get a brief summary of past errors. Every item is an object not synchronized. Note that this only makes sense should you have chosen *OX Connector continues after faulty items* (page 23).

Listing 6.4: Show all items in the morgue.

```
$ /usr/sbin/univention-ox-connector-task-management search-morgue
```

### 6.3.2 Handling errors

You can decide what to do with the items that have been moved to the morgue. All commands assume that you have the `UniventionObjectIdentifier` of that object. For each item you have the option to

1. Delete it from the list: It is as if this item never hit the OX Connector. The underlying object can of course be synchronized again if it is modified in the LDAP directory (creating a completely new item in the OX Connector's tasks).

Listing 6.5: Remove an item from the morgue.

```
$ /usr/sbin/univention-ox-connector-task-management remove-from-morgue --obj-
→id=...
```

2. Retry the very same item: The erroneous item in the list is again copied to the list of tasks, assuming that the problem is now fixed (e.g., a validation on the OX App Suite's side has been disabled).

Listing 6.6: Retry an item from the morgue.

```
$ /usr/sbin/univention-ox-connector-task-management retry-from-morgue --obj-
↳id=...
```

3. Fresh synchronization of the object: The object is again put into the list of tasks but not with the attributes it had when the synchronization happened (and failed). Instead, it is freshly fetched from the LDAP database.

Listing 6.7: Retry an item from the morgue.

```
$ /usr/sbin/univention-ox-connector-task-management resync-item --obj-id=...
```

## 6.4 Provisioning stops working

When the provisioning stopped working, a previous change in UDM is a probable reason and the OX Connector doesn't know how to proceed. The connector retries the action over and over again until an administrator repairs the cause manually.

First, see the *Log files* (page 25) and look for warnings and errors. If it's not a temporary problem like for example network connectivity, the fix requires manual action.

As a last resort, the administrator can move the task aside. The log file reveals the `Database ID` of that object (e.g. `uid=...; $object_identifier; tasks:$database_id`).

Listing 6.8: Retry an error from the list.

```
$ /usr/sbin/univention-ox-connector-task-management move-task-to-morgue --task-id=
↳$database_id --error-msg="Manual intervention after careful consideration"
```

### 6.4.1 Re-provision all data

#### Warning

Depending on the number of users and groups in the UCS LDAP directory, this task may take a lot of time.

**Reprovisioning all data isn't recommended.**

The following command reads all UDM objects from the UCS LDAP directory and adds them to the provisioning queue:

Listing 6.9: Re-provisioning all UDM objects to OX App Suite

```
$ univention-directory-listener-ctrl resync ox-connector
```

The re-provisioning won't run any *delete* operations, because the Listener only adds existing UDM objects to the queue.

#### Caution

The OX Connector may decide to delete objects based on data in the JSON files. For example `isOxGroup = Not` in a group object.

## 6.5 Duplicated *displaynames*

In OX Connector version 2.2.0 the UDM property *oxDisplayName* does not have a unique constraint anymore.

If duplicate values are used, but OX is not prepared for that, the *SOAP API* calls will fail with the following exception.

```
2023-05-30 11:59:31 WARNING Traceback (most recent call last):
2023-05-30 11:59:31 WARNING   File "/tmp/univention-ox-connector.listener_trigger",
↳ line 324, in run_on_files
2023-05-30 11:59:31 WARNING       f(obj)
2023-05-30 11:59:31 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ provisioning/__init__.py", line 86, in run
2023-05-30 11:59:31 WARNING       modify_user(obj)
2023-05-30 11:59:31 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ provisioning/users.py", line 420, in modify_user
2023-05-30 11:59:31 WARNING       user.modify()
2023-05-30 11:59:31 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ soap/backend.py", line 477, in modify
2023-05-30 11:59:31 WARNING       super(SoapUser, self).modify()
2023-05-30 11:59:31 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ soap/backend.py", line 180, in modify
2023-05-30 11:59:31 WARNING       self.service(self.context_id).change(obj)
2023-05-30 11:59:31 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ soap/services.py", line 536, in change
2023-05-30 11:59:31 WARNING       return self._call_ox('change', usrdata=user)
2023-05-30 11:59:31 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ soap/services.py", line 163, in _call_ox
2023-05-30 11:59:31 WARNING       return getattr(service, func)(**kwargs)
2023-05-30 11:59:31 WARNING   File "/usr/lib/python3.9/site-packages/zeep/proxy.py
↳ ", line 46, in _call__
2023-05-30 11:59:31 WARNING       return self._proxy._binding.send(
2023-05-30 11:59:31 WARNING   File "/usr/lib/python3.9/site-packages/zeep/wsd/
↳ bindings/soap.py", line 135, in send
2023-05-30 11:59:31 WARNING       return self.process_reply(client, operation_obj,
↳ response)
2023-05-30 11:59:31 WARNING   File "/usr/lib/python3.9/site-packages/zeep/wsd/
↳ bindings/soap.py", line 229, in process_reply
2023-05-30 11:59:31 WARNING       return self.process_error(doc, operation)
2023-05-30 11:59:31 WARNING   File "/usr/lib/python3.9/site-packages/zeep/wsd/
↳ bindings/soap.py", line 329, in process_error
2023-05-30 11:59:31 WARNING       raise Fault(
2023-05-30 11:59:31 WARNING zeep.exceptions.Fault: The displayname is already used;
↳ exceptionId 1170523631-4
```

To fix this issue, a change in the *OX App Suite* configuration is required. Add the following lines to the *user.properties* file.

```
com.openexchange.user.enforceUniqueDisplayName=false
com.openexchange.folderstorage.database.preferDisplayName=false
```

### Note

This is configured by default in the *OX App Suite* installation from the App center.



## 6.6 Traceback provisioning groups

When an ox group is synchronized, the **OX Connector** obtains information about all its users by reading from the *listener/old* directory where the latest version of the objects that have already been synchronized is stored. If any user is part of such group but is not in *listener/old*, the **OX Connector** will fail with a traceback like the following:

```
2024-11-15 16:06:33 INFO      Group oxgroup will be OX Group
2024-11-15 16:06:33 INFO      Error while processing /var/lib/univention-appcenter/
↪apps/ox-connector/data/listener/2024-11-15-15-51-31-669745.json
2024-11-15 16:06:33 INFO      This is consecutive error #11
2024-11-15 16:06:33 INFO      Sleeping for 0 sec
2024-11-15 16:06:33 WARNING Traceback (most recent call last):
2024-11-15 16:06:33 INFO      Successfully processed 0 files during this run
2024-11-15 16:06:33 WARNING   File "/tmp/univention-ox-connector.listener_trigger",
↪ line 419, in run_on_files
2024-11-15 16:06:33 WARNING       function(obj)
2024-11-15 16:06:33 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↪provisioning/__init__.py", line 115, in run
2024-11-15 16:06:33 WARNING       for new_obj in get_group_objs(obj):
2024-11-15 16:06:33 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↪provisioning/__init__.py", line 173, in get_group_objs
2024-11-15 16:06:33 WARNING       user_obj = univention.ox.provisioning.helpers.get_
↪old_obj(user)
2024-11-15 16:06:33 WARNING   File "/tmp/univention-ox-connector.listener_trigger",
↪ line 76, in _get_old_object
2024-11-15 16:06:33 WARNING       raise Exception(f"Old object file {path_to_old_
↪user} for {distinguished_name} does not exist!\nYou need to re-provision \"
↪{distinguished_name}\" (see https://docs.software-univention.de/ox-connector-app/
↪latest/troubleshooting .html#traceback-provisioning-groups).")
2024-11-15 16:06:33 WARNING Exception: Old object file /var/lib/univention-
↪appcenter/apps/ox-connector/data/listener/old/d10338de-3144-103f-8ea2-
↪f39fa7a811dd.json for uid=oxuser1,cn=users,dc=example,dc=com does not exist!
2024-11-15 16:06:33 WARNING You need to re-provision "uid=oxuser1,cn=users,
↪dc=example,dc=com" (see https://docs.software-univention.de/ox-connector-app/
↪latest/troubleshooting.html#traceback-provisioning-groups).
```

You need to re-provision the user object (*uid=oxuser1,cn=users,dc=example,dc=com* in this case) manually. Follow the instructions in *Handling errors* (page 26) to synchronize the missing users. After this manual intervention the connector automatically continues with the synchronization of the group object.

## 6.7 Collect information for support ticket

Before you open a support ticket, make sure to collect and provide relevant details about your case, so that the Univention Support team can help you:

- Provide relevant details about your environment<sup>14</sup>.
- Provide the relevant messages and tracebacks from *Log files* (page 25), specifically the *Listener Converter*.
- Describe the steps that can reproduce the faulty behavior.
- Describe the expected behavior.
- Provide data from the provisioning that causes the error.

<sup>14</sup> <https://help.univention.com/faq#posting-guidelines>

## 6.8 Invalid values for OX\_USER\_IDENTIFIER or OX\_GROUP\_IDENTIFIER

Only a UDM user property (or UDM group property in case of OX\_GROUP\_IDENTIFIER) that contains a **single value** which is **not None** is a valid option. In case a UDM property that contains an empty value or a list of values is specified, the **OX Connector** will enter an error state which needs to be resolved manually by simply setting a valid value.

Setting invalid values for the app settings *OX\_USER\_IDENTIFIER* or *OX\_GROUP\_IDENTIFIER* will lead to the following errors:

```
2024-01-11 13:57:39 WARNING Traceback (most recent call last):
2024-01-11 13:57:39 WARNING   File "/tmp/univention-ox-connector.listener_trigger",
↳ line 351, in run_on_files
2024-01-11 13:57:39 WARNING       function(obj)
2024-01-11 13:57:39 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ provisioning/__init__.py", line 86, in run
2024-01-11 13:57:39 WARNING       modify_user(obj)
2024-01-11 13:57:39 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ provisioning/users.py", line 454, in modify_user
2024-01-11 13:57:39 WARNING       user.modify()
2024-01-11 13:57:39 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ soap/backend.py", line 475, in modify
2024-01-11 13:57:39 WARNING       super(SoapUser, self).modify()
2024-01-11 13:57:39 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ soap/backend.py", line 176, in modify
2024-01-11 13:57:39 WARNING       assert self.name is not None
2024-01-11 13:57:39 WARNING No name for this attribute. Missing or misconfigured.
↳ identifier app settings
2024-01-11 13:57:39 WARNING (OX_USER_IDENTIFIER or OX_GROUP_IDENTIFIER) might be.
↳ the reason, see
2024-01-11 13:57:39 WARNING https://docs.software-univention.de/ox-connector-app/
↳ latest/troubleshooting.html#invalid-values-for-ox-user-identifier-or-ox-group-
↳ identifier
2024-01-11 13:57:39 WARNING for more information.
```

```
setting "users" udm property for groups
2024-01-11 13:59:36 WARNING Traceback (most recent call last):
2024-01-11 13:59:36 WARNING   File "/tmp/univention-ox-connector.listener_trigger",
↳ line 351, in run_on_files
2024-01-11 13:59:36 WARNING       function(obj)
2024-01-11 13:59:36 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ provisioning/__init__.py", line 108, in run
2024-01-11 13:59:36 WARNING       modify_group(new_obj)
2024-01-11 13:59:36 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ provisioning/groups.py", line 146, in modify_group
2024-01-11 13:59:36 WARNING       group.modify()
2024-01-11 13:59:36 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ soap/backend.py", line 180, in modify
2024-01-11 13:59:36 WARNING       self.service(self.context_id).change(obj)
2024-01-11 13:59:36 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ soap/services.py", line 607, in change
2024-01-11 13:59:36 WARNING       return self._call_ox('change', grp=grp)
2024-01-11 13:59:36 WARNING   File "/usr/lib/python3.9/site-packages/univention/ox/
↳ soap/services.py", line 194, in _call_ox
2024-01-11 13:59:36 WARNING       return getattr(service, func)(**kwargs)
2024-01-11 13:59:36 WARNING   File "/usr/lib/python3.9/site-packages/zeep/proxy.py
```

(continues on next page)

(continued from previous page)

```

↪", line 46, in __call__
2024-01-11 13:59:36 WARNING      return self._proxy._binding.send(
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/wsdli/
↪bindings/soap.py", line 123, in send
2024-01-11 13:59:36 WARNING      envelope, http_headers = self._create(
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/wsdli/
↪bindings/soap.py", line 73, in _create
2024-01-11 13:59:36 WARNING      serialized = operation_obj.create(*args, **kwargs)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/wsdli/
↪definitions.py", line 224, in create
2024-01-11 13:59:36 WARNING      return self.input.serialize(*args, **kwargs)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/wsdli/
↪messages/soap.py", line 79, in serialize
2024-01-11 13:59:36 WARNING      self.body.render(body, body_value)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪elements/element.py", line 232, in render
2024-01-11 13:59:36 WARNING      self._render_value_item(parent, value, render_path)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪elements/element.py", line 256, in _render_value_item
2024-01-11 13:59:36 WARNING      return self.type.render(node, value, None, render_
↪path)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪types/complex.py", line 307, in render
2024-01-11 13:59:36 WARNING      element.render(node, element_value, child_path)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪elements/indicators.py", line 256, in render
2024-01-11 13:59:36 WARNING      element.render(parent, element_value, child_path)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪elements/element.py", line 232, in render
2024-01-11 13:59:36 WARNING      self._render_value_item(parent, value, render_path)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪elements/element.py", line 255, in _render_value_item
2024-01-11 13:59:36 WARNING      return value._xsd_type.render(node, value, xsd_
↪type, render_path)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪types/complex.py", line 307, in render
2024-01-11 13:59:36 WARNING      element.render(node, element_value, child_path)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪elements/indicators.py", line 256, in render
2024-01-11 13:59:36 WARNING      element.render(parent, element_value, child_path)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪elements/element.py", line 232, in render
2024-01-11 13:59:36 WARNING      self._render_value_item(parent, value, render_path)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪elements/element.py", line 256, in _render_value_item
2024-01-11 13:59:36 WARNING      return self.type.render(node, value, None, render_
↪path)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪types/simple.py", line 96, in render
2024-01-11 13:59:36 WARNING      node.text = value if isinstance(value, etree.
↪CDATA) else self.xmlvalue(value)
2024-01-11 13:59:36 WARNING      File "/usr/lib/python3.9/site-packages/zeep/xsd/
↪types/builtins.py", line 27, in _wrapper
2024-01-11 13:59:36 WARNING      raise ValueError(
2024-01-11 13:59:36 WARNING      ValueError: The String type doesn't accept collections.
↪as value

```



## CHANGELOG

This changelog documents all notable changes to the OX Connector app. [Keep a Changelog](#)<sup>15</sup> is the format and this project adheres to [Semantic Versioning](#)<sup>16</sup>.

### 7.1 v3.0.0

Released: 2025-09-29

#### 7.1.1 Changed

The App now stores its queue of tasks in a *SQLite* database instead of having all data in JSON files. This includes the tasks as well as the data of those objects already seen. GDBM based key value stores have been removed. For now, some helper scripts will not work anymore, namely *rebuild-old.db*, *remove-from-ox-db-cache*, *check\_sync\_status.py*. Existing monitoring plugins may need adjustments.

Migration of old data is automated but may take some time depending on your environment.

#### 7.1.2 Added

The App can now be configured in a way that it *does not* stop on the first error it encounters but instead continues to process the queue. This option is deactivated by default, meaning the behavior does not change. Note that we may eventually release another version and enable that feature.

### 7.2 v2.3.5

Released: 12. August 2025

#### 7.2.1 Removed

The Resource manager field in the UMC has been removed. Ox resources still have that property in UDM, and can be edited or consulted.

There are no functional changes in the application.

### 7.3 v2.3.4

Released: 23. July 2025

---

<sup>15</sup> <https://keepachangelog.com/en/1.0.0/>

<sup>16</sup> <https://semver.org/spec/v2.0.0.html>

### 7.3.1 Fixed

Fix OX Resources UDM handler preventing the OX Connector from working with UCS 5.2-2.

## 7.4 v2.3.3

Released: 10. June 2025

### 7.4.1 Fixed

UDM now actively prevents to create an OX Context with an ID already taken by another context.

### 7.4.2 Changed

Creating a new user in OX can now convert an existing OX guest account with the same e-mail address. Note that this requires OX 8.36.36, which is currently not present in the App Center. Also note that this only works for creating users; modifying users (or similar) will not have this feature. If the OX Connector cannot send this *convertguest* flag, the old behavior applies: Guest accounts with the same e-mail address as the user being processed will block further processing until the error is resolved.

## 7.5 v2.3.2

Released: 4. June 2025

### 7.5.1 Fixed

To keep track of certain object states, the App uses an internal key value store. The keys used are the distinguished names (DNs) of the LDAP objects. These have been stored as provided in the past. From now on, the DN's are normalized and lower-cased. Existing keys in that key value store are fixed during upgrade. For that, the new command *univention-app shell ox-connector rebuild-old.db* has been added.

When a user with the same name as a context admin was changed via UDM or UMC, there was an edge case which could lead to the OX connector changing an OX context admin in the OX database. This could lead to authorization issues for OX context admins and hence to synchronization issues for the OX connector.

### 7.5.2 Changed

In certain cases, the modification of an OX user was not immediately reflected on OX' side, so that the Connector may not get the correct database ID. The App now retries in these cases a few times, assuming that the data will eventually be retrievable.

## 7.6 v2.3.1

Released: 16. Apr 2025

### 7.6.1 Added

The administrator can now specify a log level for the ox-connector, see [App Settings](#) (page 11).

### 7.6.2 Changed

The app setting `OX_CONNECTOR_LOG_LEVEL` (page 14) is used to specify the log level of the ox-connector.

### 7.6.3 Fixed

The syntax for the *oxContext* attribute has been changed from string to integer.

## 7.7 v2.3.0

Released: 27. Mar 2025

### 7.7.1 Added

Allow provisioning of [OX deputy permissions](#)<sup>17</sup> through the **OX Connector** app. OX deputy permissions allow a user to act on behalf of another user in OX App Suite, providing delegated access to email and calendars. Administrators can configure these permissions to control the level of access and actions that deputies can perform.

The administrator can now add external ca-certificates to the container, see [Import additional CA certificates](#) (page 18).

### 7.7.2 Changed

The app setting *OX\_IMAP\_LOGIN* (page 12) can contain all attribute names as placeholders. While the connector still replaces the default value `{ }` with the user's email address, you can set it to `{univentionObjectIdentifier}`, for example, given that such an attribute exists.

### 7.7.3 Fixed

Translations now work correctly.

## 7.8 v2.2.15

Released: 17. Feb 2025

### 7.8.1 Changed

Improved error message in case app settings *OX\_USER\_IDENTIFIER* or *OX\_GROUP\_IDENTIFIER* are not correctly configured.

Improve error message in case re-provisioning for a object is required.

### 7.8.2 Fixed

The documentation wasn't explicit about setting the administrative password in the app settings for the *OX Connector App*.

The internal key value store for tracking user objects handles the key (dn) case insensitive now.

## 7.9 v2.2.14

Released: 29. Oct 2024

### 7.9.1 Changed

Allow special characters for the name of the access profile.

---

<sup>17</sup> [https://documentation.open-xchange.com/8/middleware/permissions\\_and\\_capabilities/deputy\\_permission.html](https://documentation.open-xchange.com/8/middleware/permissions_and_capabilities/deputy_permission.html)

## 7.10 v2.2.13

Released: 17. Sep 2024

### 7.10.1 Changed

When changing an OX user in UDM, the OX attribute *default\_sender\_address* was left untouched. That is because it is a user preference, not “core data”. Now, if an OX user is changed in UDM so that the *primaryMailAddress* changes and this has been the user’s *default\_sender\_address*, it is overwritten to the new mail address - as this makes sense in next to all scenarios and would be considered an error if not done automatically.

## 7.11 v2.2.12

Released: 28. Aug 2024

### 7.11.1 Changed

You can now add LDAP containers to the list of default containers for functional accounts and select the container before creating a new functional account in UMC, see the [Functional accounts](#) (page 9) for more information.

## 7.12 v2.2.11

Released: 23. May 2024

### 7.12.1 Changed

Fixes a bug which prevents the removal of Open-Xchange contexts.

## 7.13 v2.2.10

Released: 26. April 2024

### 7.13.1 Changed

The performance of the OX Connector has been improved.

## 7.14 v2.2.9

Released: 12. April 2024

### 7.14.1 Added

It’s now possible to change the attribute mapping between Open-Xchange and UCS through the script `change_attribute_mapping.py`. For more information, see [User attribute mapping](#) (page 15).

## 7.15 v2.2.8

Released: 16. January 2024

### 7.15.1 Changed

The *meta.db* also stores the error message and the filename that causes the error.



### 7.15.2 Added

The script *get\_current\_error.py* outputs a json with the contents of the *meta.db*. This json can be used to automate the app health checks.

The app settings *OX\_USER\_IDENTIFIER* and *OX\_GROUP\_IDENTIFIER* have been added. They give control over which UDM property is used as the unique identifier for users and groups in OX.

The script *check\_sync\_status.py* has been added. It can be used to identify data inconsistencies between UDM, OX and the listener files.

## 7.16 v2.2.7

Released: 7. September 2023

### 7.16.1 Changed

Allow any string in *OX\_FUNCTIONAL\_ACCOUNT\_LOGIN\_TEMPLATE* app setting to simplify SSO configurations.

### 7.16.2 Fixed

Fix *OX\_FUNCTIONAL\_ACCOUNT\_LOGIN\_TEMPLATE* empty app setting handling (Bug #56523).

Fix error in context change when modifying the context and the username in the same operation (Bug #56525).

## 7.17 v2.2.6

Released: 18. August 2023

### 7.17.1 Changed

The Functional Account login field is now configurable via the app setting *OX\_FUNCTIONAL\_ACCOUNT\_LOGIN\_TEMPLATE*.

## 7.18 v2.2.5

Released: 16. August 2023

### 7.18.1 Changed

User context change uses the *UserCopy* service.

## 7.19 v2.2.4

Released: 13. July 2023

### 7.19.1 Changed

The *imaplogin* field is now configurable via the app setting *OX\_IMAP\_LOGIN*.

## 7.20 v2.2.3

Released: 27. June 2023

### **7.20.1 Fixed**

Corrected a typo in the *listener\_trigger* script.

## **7.21 v2.2.2**

Released: 22. June 2023

### **7.21.1 Fixed**

The OX-Connector now prevents a scenario in which values set by users in the App Suite app were overwritten in a wrong way.

## **7.22 v2.2.1**

Released: 07. June 2023

### **7.22.1 Changed**

The OX-Context of a group is no longer modifiable in the groups module of UMC since the OX-Context of a group is always derived from the OX-Contexts of its users.

## **7.23 v2.2.0**

Released: 01. June 2023

### **7.23.1 Changed**

Removed use of old *oxDrive* and *oxAccessUSM* UDM properties. The OX Connector only uses the *oxmail/accessprofile* objects to control access rights.

The OX Connector does not require the *oxDisplayName* to be unique anymore.

The OX connector only sets a user's *default\_sender\_address*, *language*, and *timezone* when initially creating a user. Afterwards, any user can configure their settings in the OX App suite front-end.

The OX connector can handle user files in *listener/old/* without the *oxContext* attribute.

### **7.23.2 Deprecated**

*oxTimeZone* and *oxLanguage* still exist as UDM attributes. But they are not evaluated anymore (see above in Changed; the Connector sets these attributes to the value set in the App Settings instead).

*oxDisplayName* still exists and is evaluated. At some later version, we will use the original *displayName* of a user.

## **7.24 v2.1.4**

Released: 31. May 2023

**This version has been revoked**

## **7.25 v2.1.3**

Released: 21. April 2023

### 7.25.1 Fixed

Changes to the *oxAccessUSM* attribute are now considered by the provisioning logic.

### 7.25.2 Changed

Added helper script to remove old listener files from users with empty *oxContextIDNum* attribute.

Removed *bindpwd* uses from *createextattr.py* script (#55985).

## 7.26 v2.1.2

Released: 4. April 2023

### 7.26.1 Changed

Changes in inst script for compatibility with App Center's OX App Suite.

## 7.27 v2.1.1

Released: 9. December 2022

### 7.27.1 Fixed

Fixed bug that prevented users from creating OX users from UMC.

## 7.28 v2.1.0

Released: 14. November 2022

### 7.28.1 Fixed

Remove the use of unnecessary *gid\_ox* syntax for OX group names. All valid group names in UCS are now accepted in OX.

Avoid unnecessary group *change`* operation that can fail in large groups and lead to an infinite loop where the ox-connector tries to delete an already deleted user.

Change *oxcontext contextid* syntax from string to integer.

### 7.28.2 Changed

Refactor of internal project structure.

Update of scripts and internal files.

### 7.28.3 Added

Prepare support for Univention OX App suite.

## 7.29 v2.0.1

Released: 9. September 2022

### 7.29.1 Fixed

Avoid unnecessary look-ups in the OX database when syncing groups: Users that appear to not be present in the database will be treated as such instead of double checking.

Avoid 500 log messages in OX by guarding user look-ups by an *exists* call.

## 7.30 v2.0.0

Released: 26. April 2022

### 7.30.1 Added

With OX App Suite 7.10.6 Open-Xchange added *Functional Mailboxes* to OX App Suite, see *OX App Suite - Minor Release v7.10.6 - Feature Overview* [7]. OX App Suite shares functional mailboxes among other users in the same context.

For more information, see *Functional accounts* (page 9).

## 7.31 v1.1.0

### 7.31.1 Added

OX App Suite knows access and can grant them individually to users. The **OX Connector** app supports *access profiles* through the file `ModuleAccessDefinitions.properties`.

The connector generates the file locally on the UCS system each time an administrator modifies objects in the UDM module `oxmail/accessprofile`. It doesn't provision the data to OX App Suite directly. The connector uses the *access profiles* and sets the attribute `oxAccess` during provisioning.

For limitations, see *No plausibility validation in access profile rights* (page 24).

## BIBLIOGRAPHY

- [1] *App Suite Admin Guide 7.10.5*. OX Software GmbH, 2022. URL: [https://oxpedia.org/wiki/index.php?title=AppSuite:AdminGuide\\_7.10.5](https://oxpedia.org/wiki/index.php?title=AppSuite:AdminGuide_7.10.5).
- [2] *UCS 5.2 Manual*. Univention GmbH, 2025. URL: <https://docs.software-univention.de/manual/5.2/en/>.
- [3] Raphaël Hertzog and Roland Mas. *The Debian Administrator's Handbook*, chapter Shell and Basic Commands. Freexian SARL, First edition, 2020. URL: <https://www.debian.org/doc/manuals/debian-handbook/short-remedial-course.en.html#sect.shell-and-basic-commands>.
- [4] *Referential Integrity in OpenLDAP Software 2.4 Administrator's Guide*. The OpenLDAP Project, March 2021. URL: <https://openldap.org/doc/admin24/overlays.html#Referential%20Integrity>.
- [5] *App Suite Context management*. OX Software GmbH, 2020. URL: [https://oxpedia.org/wiki/index.php?title=AppSuite:Context\\_management](https://oxpedia.org/wiki/index.php?title=AppSuite:Context_management).
- [6] *App Suite Resource management*. OX Software GmbH, 2015. URL: [https://oxpedia.org/wiki/index.php?title=AppSuite:Resource\\_management](https://oxpedia.org/wiki/index.php?title=AppSuite:Resource_management).
- [7] *OX App Suite - Minor Release v7.10.6 - Feature Overview*. OX Software GmbH, December 2021. URL: [https://www.open-xchange.com/hubfs/Imported%20files/Feature\\_Overview\\_OXAppSuite\\_7\\_10\\_6.pdf?hsLang=en](https://www.open-xchange.com/hubfs/Imported%20files/Feature_Overview_OXAppSuite_7_10_6.pdf?hsLang=en).



## A

- access profiles
  - changelog, 40
  - plausibility, 24
- administrator
  - installation, 4
- attributes
  - provisioning, 21

## C

- cache, 21
  - JSON, 21
- certificate
  - custom, 11
  - self-signed, 11
- change\_attribute\_mapping.py command line
  - option
  - dump, 16
  - modify, 15
  - restore\_default, 15
  - set, 16
  - set\_alternatives, 16
  - unset, 16
  - unset\_alternatives, 16
- changelog
  - access profiles, 40
  - functional mailbox, 40

## D

- database management script
  - log file, 25
- DEFAULT\_CONTEXT, 15
- domain admins
  - installation, 4
- dump
  - change\_attribute\_mapping.py command line option, 16

## E

- environment variable
  - DEFAULT\_CONTEXT, 11, 15
  - LOCAL\_TIMEZONE, 12
  - ox/context/id, 15
  - OX\_CONNECTOR\_LOG\_LEVEL, 14, 34
  - OX\_CONNECTOR\_STOP\_ON\_ERROR, 15
  - OX\_ENABLE\_DEPUTY\_PERMISSIONS, 14

- OX\_FUNCTIONAL\_ACCOUNT\_LOGIN\_TEMPLATE, 12
- OX\_GROUP\_IDENTIFIER, 13
- OX\_IMAP\_LOGIN, 12, 35
- OX\_IMAP\_SERVER, 11
- OX\_LANGUAGE, 12
- OX\_MASTER\_ADMIN, 3, 12
- OX\_MASTER\_PASSWORD, 3, 12
- OX\_SMTP\_SERVER, 11
- OX\_SOAP\_SERVER, 11
- OX\_USER\_IDENTIFIER, 13

## F

- files, *see* JSON
- functional mailbox
  - changelog, 40

## H

- health check
  - listener, 26
  - listener converter, 26

## I

- installation, *see* prerequisites; certificate
  - administrator, 4
  - domain admins, 4
  - other system roles, 4
  - primary directory node, 3
  - with command-line, 4
  - with web browser, 4

## J

- JSON
  - cache, 21
  - listener, 20
  - listener converter, 20

## L

- LDAP, 19
- Listener, 20
- listener
  - health check, 26
  - JSON, 20
- Listener Converter, 20
- listener converter
  - health check, 26

JSON, 20  
 log file, 25  
 log file  
   app center, 25  
   domain join, 25  
   listener converter, 25

## M

modify  
   change\_attribute\_mapping.py   command  
     line option, 15  
 Morgue, 26

## O

Old, 26  
 OX App Suite, 20  
   internal ID, 21  
   permission level, 24  
 OX Connector, 20  
 ox connector  
   other system roles, 4  
   primary directory node, 3  
 ox/context/id, 15  
 OX\_CONNECTOR\_LOG\_LEVEL, 34  
 OX\_ENABLE\_DEPUTY\_PERMISSIONS, 14  
 OX\_IMAP\_LOGIN, 35  
 OX\_MASTER\_ADMIN, 3  
 OX\_MASTER\_PASSWORD, 3  
 OX\_SOAP\_SERVER, 11

## P

permission level, *see* OX App Suite  
 prerequisites, 3  
   OX App Suite, 3  
   ucs domain, 3  
 provisioning, 20  
   attributes, 21  
   faulty item, 23, 27  
   procedure, 21  
   stopped, 27

## R

restore\_default  
   change\_attribute\_mapping.py   command  
     line option, 15

## S

Script, 20  
 --set  
   change\_attribute\_mapping.py   command  
     line option, 16  
 --set\_alternatives  
   change\_attribute\_mapping.py   command  
     line option, 16  
 SOAP API, 20  
 synchronization, *see* provisioning

## T

Tasks, 26

## U

UDM, *see* udm modules  
 udm modules, 20  
   groups/group, 20  
   oxmail/accessprofile, 20, 40  
   oxmail/functional\_account, 40  
   oxmail/oxcontext, 20  
   oxresources/oxresources, 20  
   users/user, 20  
 --unset  
   change\_attribute\_mapping.py   command  
     line option, 16  
 --unset\_alternatives  
   change\_attribute\_mapping.py   command  
     line option, 16